

FEATURES

- ❖ Easy, affordable solution for servicing septic tanks
- ❖ Designed with non-directional bristles for unrestricted flow of effluent
- ❖ Allows biological maturing and sloughing to maximize septic tank efficiency
- ❖ Provides well over 1/2 mile of filtration media with over 319 cu. in. of open area to eliminate clogging
- ❖ 2,215 sq. in. of filtering surface allow a flow rate of over 1200 GPD, filtering to 1/16" diameter
- ❖ Filtering surface is achieved with unique triangular bristle that more than doubles the filtering surface, with no uniform holes or slots to plug
- ❖ 90 degree handle for easy installation and removal
- ❖ Adapts to all types of 4" pipe
- ❖ Self-locking bristles hold the filter firmly in place, eliminating 'filter float up'
- ❖ Flexible design makes it easy to install in hard to reach places and makes replacing the filter a breeze
- ❖ Constructed of polypropylene bristles, wound together with a 316 S.S. core
- ❖ The filters designed shape creates a debris separation space which naturally sorts debris according to size and mass, ensures even filter usage for a long lifespan and maximizes circular flow



Order part No. STF-110
 STF-130

CAD detail drawing available in DXF format

RELATED PRODUCTS

- STF-110-6W page 4
- STF-110-7R page 4
- STF-110-8B page 4
- STF-130 page 14
- STF-4TEE page 14

U.S. Patent # 6, 811, 692

